

Quantum Force 9700

Security Gateway



YOU DESERVE THE BEST SECURITY



Top Security Effectiveness

Check Point #1 for the 2nd year in a row with 99.8% malware block rate in Miercom Next-Generation Firewall Security Benchmark (2024)

Named a Leader by Top Analyst Firms

Forrester Wave™ for Zero Trust Platform Providers, Q3 2023 Gartner® Firewall Magic Quadrant™ (2022)

AI/ML powered Threat Prevention

Protect networks and users from zero-days, phishing, DNS, and ransomware attacks

Hyperscale Network Security

On-demand expansion, load balancing firewall clustering, and resilient access to mission-critical applications

Unified Management and Ops Efficiency

Increase protection and reduce TCO with a consolidated security architecture

Quantum 9700 firewalls deliver up to 129 Gbps of firewall and 16.6 Gbps of threat prevention throughput with integrated AI/ML security, power efficiency and space savings in a modular 1 RU platform.

Increase the efficiency of your datacenter's security operations. Prevent even the most advanced attacks before they can infect their target. And manage your on-premises and cloud firewalls from a unified platform.







Network Resilience & Power Efficiency



Unified Security Management

9700 Performance Highlights

| Firewall | Next Gen Firewall | Threat Prevention |
|----------|-------------------|-------------------|
| 129 Gbps | 57.6 Gbps | 16.6 Gbps |



Al-Powered advanced security and uncompromising performance, built for perimeter applications and data centers

Quantum Force 9700 data center firewalls deliver high threat prevention performance in a small 1 RU form factor to protect employees, networks, and data from cyber-theft. Two network I/O slots can be configured to fit your network with a high port density of up to 8x1/10G, 4x10/25G and 2x40/100G port capacity.

Comprehensive and Industry-Leading Security

- Next Generation Firewall
- Site-to-Site and Remote Access VPN
- Application and Web Filtering
- Intrusion Prevention
- Antivirus and Anti-Bot
- Advanced DNS Security
- Sandboxing with file sanitization
- Zero-phishing (no agent required)

Highest Performance Threat Prevention

With the 9700, organizations can inspect encrypted traffic and prevent even the most evasive attacks without impacting internal network performance. Achieve 16.6 Gbps of threat prevention throughput or up to 400 Gbps of UDP 1518B firewall throughput with a single 1RU firewall.



Modular, High Port Density 1RU Chassis

The 9700 offers the flexibility to fit your changing network requirments. Populate two network I/O slots with your choice of network cards: 8x1/10G, 4x10/25G or 2x40/100G. In addition, the 40/100 card benefits for ASIC based firewall acceleration.


Power Efficient, Resilient Design

With a low power consumption per Gbps of threat prevention throughput, these large enterprise firewalls cut power costs in half when compared with similar firewalls from other vendors.

Flexible, High Performance HTTPS Inspection

While commonly used for good, HTTPS traffic can also hide illegal user activity and malicious traffic. Businesses need the ability to inspect a broad range of encrypted TLS 1.3 and HTTP/2 channels while also excluding inspection of sensitive regulated industry traffic, such as Health Care and Financial. Check Point makes it easy to fine-tune HTTPS security using customizeable dynamic security policies.







Specifications

Performance

Enterprise Test Conditions¹

| Threat Prevention ² [Gbps] | 16.6 |
|---------------------------------------|------|
| NGFW ³ [Gbps] | 57.6 |
| IPS [Gbps] | 73.7 |
| Firewall [Gbps] | 129 |

RFC 3511, 2544, 2647, 1242 Performance (Lab)

| Firewall 1518B UDP [Gbps] | 400 |
|--|--------------|
| Firewall Latency (avg) | 1.85µSec |
| VPN AES-GCM 1452B [Gbps] | 75 |
| Connections/sec | 535,000 |
| Concurrent connections (Base/Plus/Max) | 6.5M/15M/29M |

TLS Inspection Performance

| Threat Prevention ^{1,2} [Gbps] | 9.6 |
|--|-----|
| Threat Prevention ² web mix ⁴ [Gbps] | 5.8 |
| IPS web mix ⁴ [Gbps] | 7.3 |

Additional Features

Highlights

- 1 CPU, 16 physical cores, 32 virtual (total)
- Storage: BASE x 1 SSD 960GB NVMe, PLUS x 2 SSD 960GB NVMe
- Power: BASE x 1 External AC PSU, PLUS x 2 External AC PSUs
- 32 (64 in PLUS model) to 128 GB memory options
- Lights-Out-Management card optional (included in Plus package)

Network Expansion Slot Options

- 8 x 1/10GBASE-F SFP+ port card
- 4 x 10/25GBASE-F SFP28 port card
- 2 x 40/100GBASE-F QSFP28 port card

¹ Enterprise traffic profile measured with maximum memory

² Includes Firewall, App Control, URLF, IPS, Anti Malware and SandBlast (Incl. DNS Security & Zero Phishing) with logging enabled

³ Includes Firewall, App Control and IPS with logging enabled

⁴ Web traffic mix is based on NetSecOpen web traffic profile



Network

Network Connectivity

- 802.3ad passive and active link aggregation
- Layer 2 (transparent) and Layer 3 (routing) mode

High Availability

- Active/Active L2, Active/Passive L2 and L3
- · Session failover for routing change, device and link failure
- ClusterXL or VRRP

IPv₆

- NAT66, NAT64, NAT46
- CoreXL, SecureXL, HA with VRRPv3

Unicast and Multicast Routing (see SK98226)

- OSPFv2 and v3, BGP, RIP
- Static routes, Multicast routes
- Policy-based routing
- PIM-SM, PIM-SSM, PIM-DM, IGMP v2, and v3

Physical

Power Requirements

- Single Power Supply rating AC: 450W
- Power input: 100 to 240VAC (47-63Hz)
- Power consumption avg/max: 224.5W/374.3W
- Maximum thermal output AC 1277.1BTU/h

Dimensions

- Enclosure: 1RU
- Dimensions: (WxDxH): 17.2 x 20 x 1.73 in.(438 x 508 x 44mm)
- Weight: (gross; Kg): 16.9

Environmental Conditions

- Operating: 0° to 40°C, humidity 5% to 950
- Storing: -20° to 70°C, humidity 5% to 95% at 60°C
- MTBF: > 10 years

Certifications

- Safety: CB IEC 62368-1, CE LVD EN62368-1, UL62368-1, ASNZS 62368.1
- Emissions: CE, FCC IC, VCCI, ASNZS ACMA
- Environmental: ROHS, REACH, WEEE, ISO14001

Maximum Virtual System Capacity

| | Firewall VS | Firewall + IPS VS | Next Gen Threat Prevention VS |
|---------------|-------------|----------------------|----------------------------------|
| Base model | 106 | 60 | 20 |
| Plus model | 128 | 64 | 32 |
| Max capacity | 128 | 64 | 32 |
| Maestro / MHS | 128 | 64 | 32 |



Ordering Quantum Force 9700 Security Gateway

The 9700 includes 1x RJ45 (1 GbE copper) management port plus an additional 1x RJ45 (1 GbE copper) port for synchronization when using the 9700 PLUS in a cluster. With the two network I/O slots, modify the base or plus configuration to meet your networking requirements. The 40/100G ports enable firewall traffic acceleration at line-rate.

| | On Board RJ45 ¹ | 1/10 GbE Fiber | 10/25 GbE Fiber | 40/100 GbE Fiber | Memory | Redundant Power | Redundant Storage | LOM |
|---------------|----------------------------|-------------------|--------------------|---------------------|--------|--------------------|----------------------|-----|
| Base model | 6 | 4 | 0 | 0 | 32 GB | | 0 | 0 |
| Plus model | 6 | 12 | 0 | 0 | 64 GB | • | • | |
| Max capacity | 6 | 20 | 8 | 4 | 128 GB | • | • | |
| Maestro / MHS | 6 | 4 | 4 | 0 | 64 GB | | • | |

¹The RJ45 port count includes the Management & Sync ports

| SECURITY APPLIANCE ¹ | SKU |
|---|---------------------------|
| 9700 Base configuration: 1x RJ45 (1GbE Copper) management port & 1x RJ45 (1GbE Copper) sync port, on-board 4x RJ45 network ports, on-board 4x 1/10GbE SFP+ ports, 32 GB RAM, 1x 960 GB SSD NVMe, 1x AC PSUs, telescopic rails, SandBlast (SNBT) Security Subscription Package for 1 Year | CPAP-SG9700-SNBT |
| 9700 Plus configuration: 1x RJ45 (1GbE Copper) management port & 1x RJ45 (1GbE Copper) sync port, on-board 4x RJ45 network ports, on-board 4 x 1/10GbE SFP+ ports, 8 x 1/10GbE SFP+ ports, 64 GB RAM, 2x 960 GB SSD NVMe, 2x AC PSUs, Lights-Out Management (LOM), telescopic rails, SandBlast (SNBT) Security Subscription Package for 1 Year | CPAP-SG9700-PLUS-SNBT |
| Quantum Force 9700 Maestro / MHS HyperScale configuration: 1x RJ45 (1GbE Copper) management port & 1x RJ45 (1GbE Copper) sync port, on-board 4x RJ45 network ports, on-board 4 x 1/10GbE SFP+ ports, 4 x 10/25GbE SFP+ ports, 64 GB RAM, 2x 960 GB SSD NVMe, 2x AC PSU, Lights-Out Management (LOM), 2x 25GbE DAC 3M, telescopic rails, SandBlast (SNBT) Security Subscription Package for 1 Year | CPAP-SG9700-PLUS-MHS-SNBT |
| Quantum Force 9700 Maestro / MHS HyperScale configuration with 1 MHO-140 orchestrator and 2 Quantum Force 9700 appliances, each appliance includes 1x RJ45 (1GbE Copper) management port & 1x RJ45 (1GbE Copper) sync port, on-board 4x RJ45 network ports, on-board 4 x 1/10GbE SFP+ ports, 4 x 10/25GbE SFP+ ports, 64 GB RAM, 2x 960 GB SSD NVMe, 2x AC PSU, Lights-Out Management (LOM), 2x 25GbE DAC 3M, telescopic rails, SandBlast (SNBT) Security Subscription Package for 1 Year | CPAP-SG9702-PLUS-MHS-SNBT |
| Quantum Force 9700 Maestro / MHS HyperScale configuration with 1 MHO-140 orchestrator and 3 Quantum Force 9700 appliances, each appliance includes 1x RJ45 (1GbE Copper) management port & 1x RJ45 (1GbE Copper) sync port, on-board 4x RJ45 network ports, on-board 4 x 1/10GbE SFP+ ports, 4 x 10/25GbE SFP+ ports, 64 GB RAM, 2x 960 GB SSD NVMe, 2x AC PSU, Lights-Out Management (LOM), 2x 25GbE DAC 3M, telescopic rails, SandBlast (SNBT) Security Subscription Package for 1 Year | CPAP-SG9703-PLUS-MHS-SNBT |
| Next Generation Threat Prevention & SandBlast package for 1 year for Quantum Force 9700 appliance | CPSB-SNBT-9700-1Y |
| Next Generation Threat Prevention package for 1 year for Quantum Force 9700 appliance | CPSB-NGTP-9700-1Y |
| Next Generation Firewall Package for 1 year for Quantum Force 9700 appliance | CPSB-NGFW-9700-1Y |
| Quantum IoT Network Protection for 1 year for Quantum Force 9700 appliances | CPSB-IOTP-9700-1Y |
| Quantum SD-WAN subscription for 1 year for Quantum Force 9700 appliances | CPSB-SDWAN-9700-1Y |
| Data Loss Prevention (DLP) blade for 1 year for Quantum Force 9700 appliances | CPSB-DLP-9700-1Y |

¹ The Base & Plus package includes 2 virtual systems (VS)—one management VS and one production/data VS which are not additive or counted when adding additional VS licenses.



ACCESSORIES

| INTERFACE CARDS | SKU |
|---|------------------|
| 8 Port 1/10 G Base-F SFP+ interface card for 9000/19000/29000 appliances | CPAC-8-1/10F-D |
| 4 Port 10/25G Base-F SFP28 interface card for 9000/19000/29000 appliances | CPAC-4-10/25F-D |
| 2 Port 10/25/40/100G Base-F QSFP28 interface card for 9000/19000/29000 appliances | CPAC-2-40/100F-D |

| TRANSCEIVERS | SKU |
|--|--------------------------|
| Compatible with the CPAC-8-1/10F-D Interface Cards | |
| SFP transceiver module for 1000 BASE fiber ports - long range (1000BASE-LX), SM Fiber, LC | CPAC-TR-1LX-D |
| SFP transceiver module for 1000 BASE fiber ports - short range (1000BASE-SX), MM Fiber, LC | CPAC-TR-1SX-D |
| SFP transceiver to 1000 BASE-T RJ45 (Copper), CU, RJ45 | CPAC-TR-1T-D |
| Compatible with the CPAC-8-1/10F-D and CPAC-4-10/25F-D, Interface Cards | |
| SFP+ transceiver module for 10GbE fiber ports - long range (10GBASE-LR), SM Fiber, LC | CPAC-TR-10LR-D |
| SFP+ transceiver module for 10GbE fiber ports - short range (10GBASE-SR), MM Fiber, LC | CPAC-TR-10SR-D |
| SFP+ transceiver module for 10GbE fiber ports - for links up to 40km (10GBASE-ER), SM Fiber, LC | CPAC-TR-10ER-D |
| SFP+ transceiver 10GBASE-T RJ45 (Copper) - for links up to 30m over CAT6a/CAT7, CU, RJ45 | CPAC-TR-10T-D |
| Compatible with the CPAC-4-10/25F-D Interface Cards | |
| SFP28 transceiver module for 25GbE fiber ports - short range (25GBASE-SR), MM Fiber, LC | CPAC-TR-25SR-D |
| SFP28 transceiver module for 25GbE fiber ports - long range (25GBASE-LR), SM Fiber, LC | CPAC-TR-25LR-D |
| Compatible with the CPAC-2-40/100F-D Interface Card | |
| SFP+ transceiver module for 10GbE fiber ports - long range (10GBASE-LR), SM Fiber, LC with QSFP28 Adapter | CPAC-TR-10LR-D-ADP |
| SFP+ transceiver module for 10GbE fiber ports - short range (10GBASE-SR) MM Fiber, LC with QSFP28 Adapter | CPAC-TR-10SR-D-ADP |
| SFP+ transceiver module for 10GbE fiber ports - for links up to 40km (10GBASE-ER) SM Fiber, LC with QSFP28 Adapter | CPAC-TR-10ER-D-ADP |
| SFP+ transceiver 10GBASE-T RJ45 (Copper) - for links up to 30m over CAT6a/CAT7 with QSFP28 Adapter | CPAC-TR-10T-D-ADP |
| SFP28 transceiver module for 25GbE fiber ports - short range (25GBASE-SR) MM Fiber, LC with QSFP28 Adapter | CPAC-TR-25SR-D-ADP |
| SFP28 transceiver module for 25GbE fiber ports - long range (25GBASE-LR), SM Fiber, LC with QSFP28 Adapter | CPAC-TR-25LR-D-ADP |
| QSFP+ transceiver for 40GbE fiber Ports - short range (40GBASE-SR4) , MM Fiber, MPO-12 | CPAC-TR-40SR-QSFP-100m-D |
| QSFP+ transceiver module for 40GbE fiber ports - short range (40GBASE-eSR4), MM Fiber, MPO-12 | CPAC-TR-40SR-QSFP-300m-D |
| QSFP Bi-directional transceiver for 40GbE fiber ports - short range (40GBASE-SR-BD), MM Fiber, LC | CPAC-TR-40SR-QSFP-BiDi-D |
| QSFP+ transceiver module for 40GbE fiber ports for links up to 75m (40GBASE-SWDM4) MM Fiber, LC | CPAC-TR-40SWDM4 |
| QSFP+ transceiver module for 40GbE fiber ports - long range (40GBASE-LR4), SM Fiber, LC | CPAC-TR-40LR-QSFP-10Km-D |
| QSFP+ transceiver module for 40GbE fiber ports- for links up to 40km (40GBASE-ER4), SM Fiber, LC | CPAC-TR-40ER4 |
| QSFP28 transceiver module for 100GbE fiber ports - long range (100GBASE-LR4), SM Fiber, LC | CPAC-TR-100LR-D |
| QSFP28 transceiver module for 100GbE fiber ports - short range (100GBASE-SR4), MM Fiber, MPO-12 | CPAC-TR-100SR-D |
| QSFP28 Bi-directional transceiver for 100GbE fiber Ports - short range (100GBase-SR1.2 BiDi), MM Fiber, LC | CPAC-TR-100SR-BiDi |
| QSFP28 transceiver module for 100GbE fiber ports - for links up to 75m (100GBASE-SWDM4),MM Fiber, LC | CPAC-TR-100SWDM4-D |
| QSFP28 transceiver module for 100GbE fiber ports, - for links up to 40km (100GBASE-ERL4), SM Fiber, LC | CPAC-TR-100ERL4 |



| DIRECT ATTACH CABLES (DAC) | SKU |
|--|--------------------|
| 10GbE Direct Attach Cable (DAC), 3m length for CPAC-8-1/10F-D, CPAC-4-10/25F-D, and CPAC-2-40/100F-D | CPAC-DAC-10G-3M-D |
| 25GbE Direct Attach Cable (DAC), 3m length for CPAC-4-10/25F-D, and CPAC-2-40/100F-D | CPAC-DAC-25G-3M-D |
| 40GbE Direct Attach Cable (DAC), 3m length for CPAC-2-40/100F-D | CPAC-DAC-40G-3M-D |
| 100GbE Direct Attach Cable (DAC), 3m length for CPAC-2-40/100F-D | CPAC-DAC-100G-3M-D |

| MEMORY | SKU |
|--|------------------------|
| 32GB Memory upgrade kit for 9700-9800 appliances | CPAC-RAM32GB-9700/9800 |
| 64GB Memory upgrade kit for 9700-9800 appliances | CPAC-RAM64GB-9700/9800 |
| 96GB Memory upgrade kit for 9700-9800 appliances | CPAC-RAM96GB-9700/9800 |

| SPARES AND MISCELLANEOUS | SKU |
|---|-----------------------|
| 960GB SSD for 9000/19000/29000 security gateways | CPAC-SSD-960G-9000-D |
| AC PSU for 9700-9800 | CPAC-PSU-AC-9700/9800 |
| Lights-Out Management Module for 9000/19000/29000 appliances | CPAC-NLOM-D |
| Slide rails for 9000 Security Gateways (22" - 32") | CPAC-Rails-9000 |
| Telescopic slide rails for 9000 Security Gateways (24" - 36") | CPAC-RAILS-EXT-9000 |
| Blank NIC cover for 9000/19000/29000 appliances | CPAC-NIC-COVER-D |



SUBSCRIPTION SERVICES

| | NGFW | NGTP | SNBT (SandBlast) |
|---|----------|----------|---------------------|
| Application Control | ~ | ✓ | > |
| IPS | ✓ | ✓ | > |
| URL Filtering | | ✓ | ✓ |
| Anti-Bot | | ✓ | ✓ |
| Anti-Virus | | ✓ | ✓ |
| Anti-Spam | | ✓ | ✓ |
| DNS Security | | ✓ | ✓ |
| SandBlast Threat Emulation (sandboxing) | | | ✓ |
| SandBlast Threat Extraction (CDR) | | | ✓ |
| Zero Phishing | | | ✓ |
| IoT Network Protection | optional | optional | optional |
| SD-WAN Network Optimization | optional | optional | optional |

The first-year purchase includes the SNBT package. Security subscription renewals, NGFW, NGTP and SNBT are available for subsequent years.

5 Shlomo Kaplan Street, Tel Aviv 6789159, Israel | Tel: +972-3-753-4599

U.S. Headquarters

959 Skyway Road, Suite 300, San Carlos, CA 94070 | Tel: 1-800-429-4391