


# 5100 SECURITY GATEWAY



 End Of Sale  
December 31st 2020

Check Point's 5100 Next Generation Firewall offers a fully integrated, unified solution tuned to deliver maximum security against 5th generation threats without compromising performance. 5100 Security Gateway provides the most advanced threat prevention security for demanding enterprise networks.



## The Most Advanced Threat Prevention

Equipped with our SandBlast technology, protecting against unknown threats and zero-day attacks



## Full Security Uncompromising Performance

Highly optimized with up to 1.01 Gbps of threat prevention throughput



## Designed to Secure Encrypted Traffic

Powerful platforms for inspection of SSL traffic

## PERFORMANCE HIGHLIGHTS

| Gen II Security Firewall | Gen III Security NGFW <sup>1</sup> | Gen V Security Threat Prevention + SandBlast <sup>2</sup> |
|--------------------------|------------------------------------|---|
| 6.45 Gbps                | 2.1 Gbps                           | 1.01 Gbps   |

Performance measured with enterprise testing conditions. Additional performance details on page 4. 1: Includes Firewall, Application Control, and IPS. 2: Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot and SandBlast Zero-Day Protection.

WELCOME TO THE FUTURE OF CYBER SECURITY

# 5100

## Enterprise-grade security, performance and reliability

The Check Point 5100 Next Generation Security Gateway combines the most comprehensive security protections to safeguard your small enterprise and branch office deployments.

The 5100 is a 1U Next Generation Security Gateway with one I/O expansion slot for higher port capacity, an AC or DC power supply, a 1TB (HDD) or 240GB (SSD) disk, and optional Lights-Out Management (LOM) for remote management. This powerful Next Generation Security Gateway is optimized to deliver real-world threat prevention to secure your critical assets and environments.

## Key Features & Benefits

- Advanced Threat Prevention ..... 1<sup>st</sup> time prevention of known and zero-day threats
- Uncompromising Performance .... Achieve up to 1.01 Gbps of threat prevention throughput
- Secure Encrypted Traffic ..... Consolidate SSL inspection into one integrated security platform



## THE CYBER SECURITY ARCHITECTURE OF THE FUTURE

### Enterprise Security Gateways

#### ONE SECURITY PLATFORM

Leveraging unified threat intelligence and open interfaces

#### REAL-TIME THREAT PREVENTION

Blocking the most sophisticated attacks before they infiltrate the network

#### CONSOLIDATED MANAGEMENT


Single management, modular policy management and integrated threat visibility

WELCOME TO THE FUTURE OF CYBER SECURITY

## SPOTLIGHT


### 5100 SECURITY GATEWAY

- 1 Management 10/100/1000Base-T RJ45 port
- 2 RJ45/micro USB console port
- 3 One network card expansion slot
- 4 5x 10/100/1000Base-T RJ45 ports
- 5 2x USB ports for ISO installation
- 6 Lights-Out Management port



### Prevent Known and Zero-day Threats

Zero-day protection offering network security with evasion-resistant malware detection and complete protection from the most advanced attacks, ensuring quick delivery of safe content to users.



### All-inclusive Security Solutions

Check Point 5100 Next Generation Security Gateway offers a complete and consolidated security solution available in two complete packages:

- ❖ Threat Prevention
- ❖ Threat Prevention + SandBlast

### Integrated Security Management

5100 Security Appliances with the HDD option can manage itself and one adjacent appliance in a high availability deployment. Or manage the gateways via central unified management.



### Remote Management and Monitoring

A Lights-Out-Management (LOM) card provides out-of-band remote management to remotely diagnose, start, restart and manage the appliance from a remote location. Also use the LOM web interface to remotely install an OS image from an ISO file.

## ENTERPRISE-GRADE PLATFORM

|      |          | 1 GbE (copper) | 1 GbE (fiber) | Memory | LOM |
|------|----------|----------------|---------------|--------|-----|
| 5100 | Base     | 6              | 0             | 8 GB   | ○   |
|      | HPP      | 6              | 4             | 16 GB  | ●   |
|      | Maximums | 14             | 4             | 16 GB  | ●   |

○ this is optional

WELCOME TO THE FUTURE OF CYBER SECURITY

## Performance

### Enterprise Testing Conditions

- 1.01 Gbps of Threat Prevention<sup>1</sup>
- 2.1 Gbps of NGFW<sup>2</sup>
- 2.45 Gbps IPS
- 6.45 Gbps of firewall throughput

### Ideal Testing Conditions

- 14.5 Gbps of UDP 1518 byte packet firewall throughput
- 1.6 Gbps of AES-128 VPN throughput
- 110,000 connections per second, 64 byte response<sup>3</sup>
- 3.2/6.4M concurrent connections, 64 byte response<sup>3</sup>

1: Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot and SandBlast Zero-Day Protection. 2: Includes Firewall, Application Control and IPS. 3: Performance measured with default/maximum memory with R80.10.

## Additional Features

### Highlights

- 1x CPUs, 2x physical cores (total)
- 1x 1TB HDD or 240GB SSD storage
- 8 and 16 GB memory options
- 1x AC or DC power supply
- Lights-Out-Management card is optional

### Network Expansion Slot Options (1 of 1 slots open)

- 8x 10/100/1000Base-T RJ45 port card, up to 14 ports
- 4x 1000Base-F SFP port card, up to 4 ports

### Fail-Open/Bypass Network Options

- 4x 10/100/1000Base-T RJ45 port card

## Content Security

### First Time Prevention Capabilities

- CPU-level, OS-level and static file analysis
- File disarm and reconstruction via Threat Extraction
- Average emulation time for unknown files that require full sandbox evaluation is under 100 seconds
- Maximal file size for Emulation is 100 MB
- Emulation OS Support: Windows XP, 7, 8.1, 10

### Applications

- Use 8,000+ pre-defined or customize your own applications
- Accept, prevent, schedule, and apply traffic-shaping

### Data Loss Prevention

- Classify 700+ pre-defined data types
- End user and data owner incident handling

## Content Security (continued)

### Dynamic User-based Policy

- Integrates with Microsoft AD, LDAP, RADIUS, Cisco pxGrid, Terminal Servers and with 3<sup>rd</sup> parties via a Web API
- Enforce consistent policy for local and remote users on Windows, macOS, Linux, Android and Apple iOS platforms

## Network

### Network Connectivity

- Total physical and virtual (VLAN) interfaces per appliance: 1024/4096 (single gateway/with virtual systems)
- 802.3ad passive and active link aggregation
- Layer 2 (transparent) and Layer 3 (routing) mode

### High Availability

- Active/Active L2, Active/Passive L2 and L3
- Session failover for routing change, device and link failure
- ClusterXL or VRRP

### IPv6

- NAT66, NAT64, NAT46
- CoreXL, SecureXL, HA with VRRPv3

### Unicast and Multicast Routing (see SK98226)

- OSPFv2 and v3, BGP, RIP
- Static routes, Multicast routes
- Policy-based routing
- PIM-SM, PIM-SSM, PIM-DM, IGMP v2, and v3

## Physical

### Power Requirements

- Single Power Supply rating: 250W/300W
- AC power input: 90 to 264V (47-63Hz)
- Power consumption max: 62.9W
- Maximum thermal output: 214.6 BTU/hr.

### Dimensions

- Enclosure: 1RU
- Dimensions (WxDxH): 17.2x16x1.73 in.(438x406.5x44mm)
- Weight: 13.7 lbs. (6.22 kg)

### Environmental Conditions

- Operating: 0° to 40°C, humidity 5% to 95%
- Storage: -20° to 70°C, humidity 5% to 95% at 60°C

### Certifications

- Safety: UL, CB, CE, TUV GS
- Emissions: FCC, CE, VCCI, RCM/C-Tick
- Environmental: RoHS, WEEE, REACH<sup>1</sup>, ISO14001<sup>1</sup>

<sup>1</sup> factory certificate

WELCOME TO THE FUTURE OF CYBER SECURITY

## ORDERING 5100 SECURITY GATEWAYS

| BASE CONFIGURATION <sup>1</sup>   | SKU                  |
|---|----------------------|
| 5100 Next Generation Security Gateway Base Configuration, includes 6x1GbE copper ports, 8GB RAM, 1 HDD, 1 AC Power Unit, Next Generation Threat Prevention (NGTP) Security Subscription Package for 1 Year  | CPAP-SG5100-NGTP     |
| 5100 SandBlast Next Generation Security Gateway Base Configuration, includes 6x1GbE copper ports, 8GB RAM, 1 HDD, 1 AC Power Unit, SandBlast (NGTX) Security Subscription Package for 1 Year  | CPAP-SG5100-NGTX     |
| HPP CONFIGURATION <sup>1</sup>  | SKU                  |
| 5100 Next Generation Security Gateway with High Performance Package, includes 6x1GbE copper ports, 4x1Gb SFP ports, 4 SR transceivers, 16 GB RAM, 1 HDD, 1 AC Power Unit, Lights Out Management (LOM), Next Generation Threat Prevention (NGTP) Security Subscription Package for 1 Year      | CPAP-SG5100-NGTP-HPP |
| 5100 Next Generation Security Gateway with High Performance Package, includes 6x1GbE copper ports, 4x1Gb SFP ports, 4 SR transceivers, 16 GB RAM, 1 HDD, 1 AC Power Unit, Lights Out Management (LOM), Next Generation Threat Extraction (SandBlast) Security Subscription Package for 1 Year | CPAP-SG5100-NGTX-HPP |

<sup>1</sup> 2 and 3 year, Virtual Systems packages and DC power options also available in the online product catalog

### Accessories

| INTERFACE CARDS AND TRANSCEIVERS  |                     |
|---|---------------------|
| 8 Port 10/100/1000 Base-T RJ45 interface card                                       | CPAC-8-1C-B         |
| 4 Port 1000Base-F SFP interface card; requires additional 1000Base SFP transceivers | CPAC-4-1F-B         |
| SFP transceiver module for 1G fiber ports - long range (1000Base-LX)                | CPAC-TR-1LX-B       |
| SFP transceiver module for 1G fiber ports - short range (1000Base-SX)               | CPAC-TR-1SX-B       |
| SFP transceiver to 1000 Base-T RJ45 (Copper)  | CPAC-TR-1T-B        |
| 4 Port 1GE copper Bypass (Fail-Open) network interface card (10/100/1000 Base-T)    | CPAC-4-1C-BP-B      |
| MEMORY  | SKU                 |
| Memory upgrade kit from 8GB to 16GB for 5100 appliance                              | CPAC-RAM8GB-5000    |
| SPARES AND MISCELLANEOUS  | SKU                 |
| Lights Out Management module  | CPAC-LOM-B          |
| Slide rails for 5000 Appliances (22" - 32")   | CPAC-RAILS-5000     |
| Extended slide rails for 5000 Appliances (24" - 36")                                | CPAC-RAILS-EXT-5000 |

Note: for returns of existing security gateways via the RMA process, a 500GB HDD is available